



80-108 Light weight broad acre disc plough



GRIZZLY'S SANDGROPER has been designed to fill a gap in our range, a gap which our competitors have enjoyed until now.

It has reduced weight and cost.

Suitable for lighter soils where only a few inches of penetration is required, while still cutting out weeds and leaving a level "seed bed" finish.

Reduced weight makes it ideal for rocky

conditions, with less chance of bringing unwanted rocks to the surface. The **SANDGROPER** will have the competition worried.

> No excess weight where it is not needed. More price competitive. Utilizes the proven Grumpy style running gear. Three gang angles for versatility. Folding Wing design follows ground formation.





Uses existing proven features. Up To 26" discs to still provide effective cut out on 9" spacings. Choice of 3 gang angles to allow full cut out in shallow working. The Sandgroper is still a true tandem offset sics plough.

Dual tyres give maximum flotation in light country and give increased support when road transporting.

(Flotation options Available)





PROUDLY DESIGNED AND MANUFACTURED IN AUSTRALIA BY GRIZZLY ENGINEERING PTY LTD E-mail: grizzly@swanhill.net.au Phone. 1800 637 250 Tollfree Phone. 03 5032 9155 Fax: 03 5032 9280

SANDGROPER SPECIFICATIONS

MODEL	SG80	SG84	SG92	SG100	SG108
Hectares @8kph	7.0	7.3	8.0	8.9	9.6
Disc Spacing	230mm	230mm	230mm	230mm	230mm
	9"	9"	9"	9"	9"
Total Weight approx	5.850kg	6.150kg	6650kg	7.000kg	7.480kg
Disc Weight approx	73kg	72kg	72kg	70kg	69.25kg
Cutting Width @ 21 degrees	8.4m	9.4m	10.2m	11.1m	12.0m
Transport Height	4.1m	4.3m	4.75m	4.77m	5.0m
Transport Width	5.2m	5.2m	5.2m	5.96m	5.96m
No. Bearings	40	40	40	40	48
No. Tyres	8	8	8	8	8
Tyre Size	(9.00 x 16) 10 ply (option 12.0 x 16) 12 Ply (12.5/80 x 18) 16 Ply				
Hydraulic Pitch Control	2.5" x 6" Hydraulic Pitch Control & Level Spring Assembly				
Hydraulics Lift	3 ³ / ₄ "x12, 4"x12, 4 ¹ / ₄ "x12, 4 ¹ / ₂ "x12 4 ¹ / ₄ "x12, 4 ¹ / ₂ "x12, 4 ³ / ₄ "x12, 5"x12				
Hydraulic Wings	4 x 48" 2 off				
Stub Axle Size	60mm				
Main Frame	150 x 100 x 6 RHS (Grade 350) (6" x 4" x ¼")				
Gang Frame	200 x 100 x 6 RHS (Grade 350) (8" x 4" x ¼")				
Gang Axles	19 / 21 / 23 degrees				
Gang Bearings	28.6mm (1 1/8") SQ Duraflex				
Gang Bolts	4 x 16mm Grade 5.8				
Scrapers	Grizzly Floppy T Bar Scrapers				
Spool Size	150mm Seamless Heavy Wall Pipe				
Pull Size	150 x 150 x 9 RHS (Grade 350) (6" x 6" x 3/8")				
Pull Tongue	Fixed 70mm Thick x 50mm Hole				
Disc Size	610mm x 5mm (24" x 3/16") Fluted (Optional 26" available)				
Filler Discs	510mm x 4mm (20" x 5/32")				
N.R. Design and Specifications are subject to shance without prior notice					

N.B.: Design and Specifications are subject to change without prior notice.