

2581 Hydraulic Harrow Bar

The K-Line Industries 2581 SJ Hydraulic Harrow Bar is rugged and reliable, engineered for many hectares of dependable harrowing and trash raking on large broadacre farming properties.



Induction hardened pins, precision machining in the universal joint, extra heavy duty frame construction and 2.5T axles have been incorporated into the design for harsh Australian field conditions.

For operator safety, the cables fold automatically. Simply lift harrows and drive forward for transport (wings trail behind). Reverse when preparing for work so wings are spread 180° and lower to working position. (Safety pins are provided for transport).

- Working width - 24.94m (81'18")
- Extra heavy duty construction - 200mm SHS mainbeam
- Universal joints - 2" induction hardened pins precision machined with seals
- Auto fold cables for tractor seat operation
- Suits 90lb, 130lb, 190lb Stump Jump Harrows
- Ideal for dumping trash

SPECIFICATIONS 2581 SJ HARROW BAR

Operating width	24.9m (81'8")	Wheel equipment	6x11.5/80 - 15.3
Transport width (approx)	5.0m approx	Hydraulic cylinders	2x(30"x4")
Harrow sections	29	Jack equipment	3x KH150
No. on each wing	13	Cable equipment	2x(18x11.56m)
No. on centre	3	A-Frame construction	200x100 RHS
Uni-Joint Pin Size	2"	Mainbeam construction (Wing)	200 SHS

DUE TO CONTINUAL PRODUCT DEVELOPMENT, DESIGN AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE