

CROPCOMMANDER

PRECISION SEEDING SYSTEM



COMPACT AND VERSATILE! Depending on model, folds to 3.5m width for easy road travel

FREE CALL: 1800 194 131

www.k-line.net.au

sales@k-line.net.au





CROPCOMMANDER

FITTED WITH OPTIONAL COULTER SYSTEM

- ✓ Reduced soil throw for higher operating speeds
- ✓ Greater trash handling ability



Canola – 25 days



Canola – 57 days



Canola – 105 days



Canola – 140 days



HOW IT WORKS



HIGHER YIELDS
HIGHER PROFITS

CROPCOMMANDER System Combines **three** in **one!!**

- ✓ Precision Seeding
- ✓ Deep banding of fertilizer
- ✓ Soil disturbance for root structure development



CROPCOMMANDER

Features

What it means for you

Primary Tine (high breakout)
Fractured soil below seed line for potential root development

- More rapid root development
- Better fertilizer uptake
- Less seed burn

Secondary Tine (seeding)
Advanced CROPCOMMANDER design

- No rebound shock from primary tine to seeding tine assembly
- Accurate ground following seed placement
- Adjustable seed placement position
- Optional profile press wheels with adjustable down pressure

High underframe

- Superior design allows better flow of residue through machine

Coulter System (optional)

- Less soil throw
- Higher operating speeds
- Cuts through heavy trash residue

“The K-Line Twin Tine System with the deep banding of fertilizer proves very beneficial in a one pass operation especially in tight soils where this high break out primary tine caused a fracturing effect in the root development area, which resulted in vigorous crop growth.”

York Ridge Enterprises, Farmer - Cowra NSW

“The secondary tine in association with the press wheel enables me to accurately control seed depth of canola, wheat, oats and various pasture species”

Farmer - Cowra NSW

**NARROW
TRANSPORT
WIDTH**

**For easy
road travel!**





Wheat – 20 days

CROPCOMMANDER is a precision seeding system which has been developed after extensive research by our design team in conjunction with farmers and agronomists.

The twin tine system is followed by a press wheel with variable down pressure.

The primary tine has a high breakout for deep banding and fertilizer application.

The secondary seeding tine is ground following for precision seed placement.

Compact and versatile, this precision sowing machine sets a new standard in agriculture.

“The high breakout pressure of the primary tine has enabled me to place Big N at a depth of 10cm, well below the seed. This deep cultivation has also dealt with any issues of Rhizoctonia”

Ross Graham, Farmer - Cowra NSW

"The K-Line seeder has been a worthwhile addition to my farming operation, enabling me to perform my seeding operations in one pass"

Ross Graham, Farmer - Cowra NSW

CROP COMMANDER

Specifications

Sowing width	5-8m
Row spacing	230-305mm
Transport width	From 3.5m
Tyre size	400/60 x 22.5

Options

Press wheel profiles
Hydraulic tine
Tow hitch
Front Coulters



FREE CALL: 1800 194 131
www.k-line.net.au
sales@k-line.net.au